


Zip Dee NX Patio Awning OPERATION

TO OPEN THE AWNING (After Step 3, complete steps 4-6 at each end of awning)


1. UNLOCK Z-LOCK



Insert the pull rod into the Z-Lock lever and pull down.


WARNING: LEAVE Z-LOCK OPEN WHEN AWNING IS OPEN TO AVOID DAMAGE

2. UNLOCK TRAVEL LATCH




Insert the pull rod into the travel latch loop and rotate open

3. UNROLL FABRIC



Insert the pull rod into the loop of the strap and pull the awning all the way out. Step under the awning and fold or roll the strap and tuck it into the fabric storage loop.

4. EXTEND RAFTER



Rafter Arm





Fig. 4a


Standing under the awning, lift the Rafter Arm off the storage stud, extend and place the "claw" casting over the shaft of the roller (fig. 4a).

5. LOCK RAFTER



Lock the rafter arm in position by pressing down on the steel main arm until the ratchet stud clicks. At this point the fabric will be taut.

*6. RAISE ROLLER




Raise the awning to the desired height by releasing the snap stud on the main arm and pushing up and outward on the roller assembly.

* If Slider Bar is installed, raise one hole lower. See separate instructions.


TO CLOSE THE AWNING (Perform steps 1 & 2 at each end, then Step 3)

1. LOWER ROLLER




Release the snap stud of the main arm and lower the awning to its lowest position.

2. STORE RAFTER ARM



Release the ratchet stud (pull outward on the cap). Lift the claw from the roller shaft and place it on the stud located on the inside of the main arm.



3. ROLL CLOSED



Hold the end of the strap then push the roller up briskly until you feel the spring take over. Control the speed with the strap. Spiral diagonally to prevent buildup. When the roller reaches the cover, release the strap and let the awning roll freely the rest of the way.

4. ENGAGE ALL TRAVEL LOCKS

A. Lock the awning in place by flipping the Z-Lock lever into the "closed" position using the pull rod.



B. Insert Pull Rod into Travel Latch loop and twist shut.